Application No. <u>09/912,316</u> Amendment dated November 7, 2003 Page 3

Amendments to the Claims:

The following claims will replace all prior versions of the claims in this application (in the unlikely event that no claims follow herein, the previously pending claims will remain):

- (Currently amended) A refrigeration lubricant composition suitable for use in a
 refrigeration system with a refrigerant containing a hydrofluorocarbon and/or a
 hydrochlorofluorocarbon, comprising consisting essentially of a synthetic lubricant
 containing consisting essentially of a polyol ester and/or a polyalkylene glycol and an
 amphiphilic anti-deposition component which is anionic and contains a non-polar part to the
 molecule which contains a fluorocarbon group.
- 2-3. (Cancelled).
- 4. (Original) A composition according to claim 1 in which the amphiphilic antideposition component is such that in the Dispersibility Test described herein, the phases of R134a and the total oil mixture separate after at least 10 seconds.
- 5-8. (Cancelled).
- (Previously presented) A composition according to claim 1 or claim 4 in which the anti-deposition component is present at a level of 0.001 to 5% based on the weight of the hybricant.
- 10. (Currently amended) A composition according to claim 1 in which the lubricant emprises polyol ester and/or polyalkylene glycol is a compound of the general formula (II):

 R(OC(O)R¹) R(OC(O)R¹)_n (II)

wherein R is a hydrocarbon radical remaining after removing the hydroxyl groups from pentaerythritol, dipentaerythritol, tripentaerythritol, trimethylol ethane, trimethylol propane or neopentyl glycol, or the hydroxyl containing hydrocarbon radical remaining after removing a proportion of the hydroxyl groups from pentaerythritol, dipentaerythritol,

30410471v1

Application No. <u>09/912,316</u> Amendment dated November 7, 2003 Page 4

tripentaerythritol, trimethylol ethane, trimethylol propane or neopentyl glycol; each R^1 is, independently, H, a straight chain aliphatic hydrocarbyl group, a branched chain aliphatic hydrocarbyl group, an aliphatic hydrocarbyl group containing a carboxylic acid or carboxylic acid ester substituent, provided that at least one R^1 group is a linear aliphatic hydrocarbyl group or branched aliphatic hydrocarbyl group; and n is an integer.

- 11. (Original) A composition according to claim 10 in which the ester comprises an ester of pentaerythritol, dipentaerythritol and/or tri pentaerythritol and each R¹ is selected from a straight chain aliphatic hydrocarbyl group and a branched chain aliphatic hydrocarbyl group.
- 12. (Cancelled).
- 13. (Previously presented) A refrigerant composition comprising the refrigeration lubricant composition according to claim 1, and a refrigerant, in which the refrigerant comprises 1,1,1,2-tetrafluoroethane.
- 14. (Previously presented) A refrigerant composition comprising the refrigeration lubricant composition according to claim 1, and a refrigerant, in which the refrigerant comprises a blend of 2 or more hydrofluorocarbon refrigerants.
- 15. (Previously presented) A refrigeration system comprising a compressor, a condenser, an expansion device and an evaporator linked to form a loop in which a refrigerant circulates and is successively condensed and evaporated so as to provide a refrigeration effect the refrigerant comprising a hydrofluorocarbon and/or a hydrochlorofluorocarbon refrigerant, and the system further containing a refrigeration lubricant composition as defined in claim 1.
- 16. (Cancelled).

30410471v1

Application No. <u>09/912,316</u> Amendment dated November 7, 2003 Page 5

- 17. (Original) A method of inhibiting the deposition of or removing unwanted residues in a refrigeration system which comprises operating a refrigeration system when charged with a hydrogen-containing refrigerant and a refrigeration lubricant composition as defined in claim 1.
- 18. (Original) A method according to claim 17 including the steps of operating the refrigeration system containing a refrigerant and a lubricant, adding the anti-deposition component to the system, and operating the system further so as to inhibit deposition or remove deposits of unwanted residues.
- 19. (Currently amended) A refrigeration lubricant composition comprising consisting essentially of a synthetic lubricant consisting of a polyol ester and/or a polyalkylene glycol and an amphiphilic anti-deposition component which is an alkyl alkoxylate derived from an alkylene oxide and a moiety derived from a compound having an active hydrogen atom and an oleophilic moiety, an ester of a polyalkylene glycol or a fluorinated polyether.
- 20. (Currently amended) A refrigeration lubricant composition emprising consisting essentially of a synthetic lubricant consisting of a polyol ester and/or a polyalkylene glycol and an amphiphilic anti-deposition component which is a dialkylsulphonsuccinate, a salt thereof, a fluoroaliphatic polymeric ester, a comb graft copolymer of methyl methacrylate/methacrylic acid/methoxy polyethyleneoxide methacrylate, or a solution of an acrylic graft copolymer.

30410471v1